



## FEEL SILK COLLECTION

### DESCRIPTION :

Water-based paint for interior, acrylic-based water-containing mixes with a color paste:  
Suitable carriers are completely smooth surfaces and little absorbent.

### DESTINATION :

It's Paint suitable for wall designs and particularly refined ceilings with beautiful colors and shades satin appearance.

### COMPOSITION :

acrylic resin, pigments and fillers, additives -teinte.

### TECHNICAL FEATURES :

Colors	Dispersion in the acrylic resin
Aspect of the dry film	Matt satin
Viscosity	pasty
Density	10600 $\pm$ 500 cps
Rendement	160-200 ml/m <sup>2</sup> resp. 5-6 m <sup>2</sup> /liter
Gravity	1.300 $\pm$ 0,02 Kg/liter
Drying	4 hours
Fire rating class	M - 1(UNE 2327)
Recoverable	12-24 hours
Content COY (Cat. Ala)	maximum content 30g/1
Packing	1Kg ; 3Kg

### APPLICATION AND DILUTION :

Mix well until homogenization of the product.

Application way: roller, pallet and plastic trowel

Diluent: water

Dilution ratio: depending on use

Cleaning: with water.

### USE CAUTION :

Do not apply at temperatures below + 5°C and above + 30°C. Do not work on heated supports.

### SURFACE PREPARATION :

The surface must be dry and free of salts or other contaminants.

For new walls, we recommend waiting for at least two weeks before applying the product.  
desirable that the surface is smooth and regular.

### CONDITIONNEMENT :

In packaging of 1Kg - 3Kg.

### STORAGE AND SHELF :

Fresh, however, store away from frost. Reseal the buckets and start uses it quickly. The original pails must be closed and undyed and kept for at least 24 months.

### SAFETY DATA :

**PRODUCT NOT FLAMMABLE**, it does not require special labeling according to dangerous regulations.

### NOTE :

The data reported above are based on our current technical knowledge and experiences.  
But it's impossible to control the conditions of application; the manufacturer assumes no responsibility derived from the use of our products. This plugit cancels anypreviouslypublished.