



## SATIN SILVER COLLECTION

### DESCRIPTION :

Water-based paint for the interior, water containing acrylic-based mixes with different colors: suitable carriers are completely smooth surfaces and little absorbent.

### DESTINATION :

It's paint suitable for wall designs and particularly refined ceilings with beautiful colors and shades satin.

### COMPOSITION :

Acrylic resin, pigments and fillers, additives tint.

### TECHNICAL FEATURES :

Color	Under the shade
Dilution	Ready to use
Aspect of the dry film	Matt satin
Viscosity	Liquid
Density	10600 ± 500 cps
Yield	8-9 m <sup>2</sup> /Kg
Gravity	1.140 +0,10 Kg/liter
Drying	4 hours
Fire rating class	M - 1(UNE 2327)
Recoverable	12-24 hours
content COY (Cat. Ala)	Maximum content 30g/1
Packing	1,1 L ; 3,6 L

### APPLICATION AND DILUTION :

Mix well until the product homogenization.

Application: roller, pallet and plastic float.

Diluent: water.

Dilution ratio: by use.

Cleaning: with water.

### USE CAUTION :

Do not apply at temperatures below + 5C° and above + 30 C°.

Do not work on heated substrates.

### SURFACE PREPARATION: :

The surface must be dry and free of salts or other contaminants.

For new walls, we recommend waiting at least two weeks before applying the product. It is desirable that the surface is smooth and regular.

### PACKAGING :

In packaging of: 1KG, 3KG.

### STORAGE AND SHELF :

Cool, however, store away from frost. Reseal the buckets and start uses it quickly. The original pails must be closed and undyed keep for at least 24 months.

### SAFETY DATA :

**PRODUCT NOT FLAMMABLE**, it requires no special hazard label according to regulations.

### NOTE :

The data reported above are based on our current technical knowledge and experiences. But it's impossible to control the conditions of application; the manufacturer assumes no responsibility derived from the use of our products. This plugit cancels any previously published.