

## DESCRIPTION :

LEONARDO SILTED is characterized by attractively finishes that is distinguished by precious metallic reflections and micron of sand that stand out to give a dark light effect and also a fantastic pearly effect. It also provides very nice touch with the particularity of LEONARDO silted ensures excellent flexibility in its implementation. It creates an elegance in the conventional and unconventional environments. It also stands in modern environments such as public and private places. LEONARDO SILTED is inflammable and becomes completely washable after 3 weeks.

## DESTINATION :

Water-based paint for interiors with sandy hues, semi-gloss. Leonardo silted perspirant product is a washable with water and detergents common after 15 days.

## COMPOSITION :

Special pigments and acrylic resins + Solvents: water

## CARACTERISTIQUE TECHNIQUES :

|                        |  |
|------------------------|--|
| Color                  | ARGENT   |
| Dilution               |  |
| Aspect of the dry film | Matt satin   |
| Viscosity              | 10600 $\pm$ 500 cps                                |
| Density                | 10600 $\pm$ 500 cps                                |
| Yield                  | 10 m <sup>2</sup> /L for one layer                 |
| Gravity                | 1.062 $\pm$ 0,02 kg/liter                          |
| Drying                 | the powder after 2 hours at 20°C;<br>dry after 8 H |
| Fire rating class      | M - 1(UNE 2327)                                    |
| Recoverable            | 12-24 hours  |
| Content COY (Cat. Ala) | Maximum content 30g/1                              |
| Packaging              | 1L ; 3,6 L ; 10L                                   |

## APPLICATION AND DILUTION :

Mix well until homogenization of the pot.

Application: roller, spray

Dilution proportion: according to use.

Dilution: to use if the application is done with a brush; with %5 water

Cleaning : with water.

## USE CAUTION :

Application temperature: brush between +5°C and +35°C; spray also more than 40°C.

Do not apply to an ambient temperature less than 5°C and above 30°C.

Do not work on heated substrates.

## SURFACE PREPARATION :

The surface must be dry and free of salts or other contaminants.

For new walls, we recommend waiting at least two weeks before applying the product. It is desirable that the surface is smooth and regular. With pc that is between 5 10 to 10%.

## PACKAGING :

In packaging of: 1KG; 3KG.

## STORAGE AND SHELF :

Storage: in well closed box, and after use, store neither at a temperature not lower than + 5 ° C nor above + 35°C.

Stability: approximately 1 year.

Cool, however, store away from frost. Reseal the buckets and start to use it quickly. The original pails closed and undyed kept for at least 24 months.

## SAFETY DATA :

**PRODUCT NOT FLAMMABLE**, it does not require special labeling according to dangerous regulations.

## NOTE :

The data reported above are based on our current technical knowledge and experiences. But it's impossible to control the conditions of application; the manufacturer assumes no responsibility derived from the use of our products. This plugit cancels any previously published.

SILTED  
COLLECTION

