

DESCRIPTION :

The GRAFFIATO is presented as a smooth paste. It consists of acrylic resins that are manufactured based on water as well as pigments resistant to UV rays.

DESTINATION :

It is a painting dedicated to the outer wall decoration in general. It is used for protection and decoration of facades as well as for renovations. The GRAFFIATO product is generally used for homes, hotels, buildings ... etc.

COMPOSITION :

Emulsion acrylic resin, pigments, and special additives.

TECHNICAL FEATURES :

Colors	color sheet
Dilution	Ready to use – may be diluted with a little water
Aspect of the dry film	Mat
Viscosity	Dough
Density	10600 ± 500 cps
Yield	3,5 - 4 Kg / m ²
Gravity	1800± 50 g/ l
Drying	4-5 hours
Recoverable	12-24 hours.
Content COY (Cat. Ala)	Maximum content 30g/l
Packing	20 Kg

APPLICATION AND DILUTION :

Mix well until homogenization of the pot.

Tools: metal trowel (Stainless steel) or plastic (second layer)

Application: Apply with a steel trowel, a single homogeneous and continuous layer and successively to not fully dry layer.

Diluent: Ready to use, possibly adding a small amount of water to consistency.

Dilution ratio: by use

Cleaning: with water

USE CAUTION :

Product application is done in a temperature equivalent to: min + 5 ° C + 40 ° C max.

Relative Humidity Ambient: max %80. The supports must not be frozen or moist.

SURFACE PREPARATION :

All substrates must be carefully prepared by hand brushing and / or washing with hydro polishing machine according to the nature and dirt deposited on the surfaces to be treated.

Inconsistent old paintings or detach phase must be removed.

It is advisable to apply a coat of primer diluted at %30 with water.

PACKAGING :

In packaging of 20 Kg.

STORAGE AND SHELF :

24 months without increase in viscosity in the original package tightly closed. The cube must be kept safe from extreme temperatures below 0 ° C and above 35 ° C.

SAFETY DATA :

PRODUCT NOT FLAMMABLE, it requires no special hazard label according to regulations.

NOTE :

The data reported above are based on our current technical knowledge and experiences. But it's impossible to control the conditions of application; the manufacturer assumes no responsibility derived from the use of our products. This plug it cancels any previously published.

GRAFFIATO
EXTERIOR

