### DESCRIPTION :

Water-based paint for interior, acrylic-based water-containing: suitable carriers are completely smooth surfaces and little absorbent.

DESTINATION :

It's paint suitable for wall designs and particularly refined ceilings with beautiful colors.

### COMPOSITION :

Acrylic resin, pigments and fillers, additives -teinte. TECHNICAL FEATURES :

Colors	According to reference
Dilution	Ready to use
Aspect of the dry film	Matt
Viscosity	Liquid
Density	10600 ± 500 cps
Yield	8-9 m² for 1coat
Gravity	1.003 ± 30 gr/LT. at 20°C
Drying	in surface. 30 - 45 minutes at 20°C 2ed coat : 5 - 6 hours at 20°C In depth 24 hours at 20°C
Fire rating class	M1-(UNE 2327)
Recoverable	12-24 hours
Content COY (Cat. Ala)	
Packing	1KG, 3KG

# APPLICATION ET DILUTION :

Mix well until homogenization of the product.

Application way: roller, palette, plastic trowel and buffers. Diluent: water Dilution ratio: depending on usage Cleaning: with water.

### USE CAUTION :

Do not apply at temperatures below + 5 C° and above + 30 C°. Do not work on heated supports.

# SURFACE PREPARATION :

The surface must be dry and free of salts or other contaminants.

For new walls, we recommend waiting at least two weeks before applying the product. Place the sandpaper, dust, chew imperfections with putty, let it dry for at least 4 hours and apply one or two coats of PRIMER 300 D white or lightly pigmented suitably diluted. Interleave between layers at least 4-5 hours. It is desirable that the surface is smooth and regular.

### PACKAGING :

In packaging of : 1KG, 3KG

### STORAGE AND SHELF :

Cool, however, store away from frost. Reseal the buckets and started running fast. The original pails closed and undyed keep for at least 24 months.

# SAFETY DATA :

**PRODUCT NOT FLAMMABLE,** it requires no special hazard label according to regulations.

# NOTE :

The data reported above are based on our current technical knowledge and experiences. But it's impossible to control the conditions of application; the manufacturer assumes no responsibility derived from the use of our products. This plug it cancels any previously published.

